

[illegible]

MM	MM	TTTTTTTTT	AAAAAA	DDDDDDDD	EEEEEEEEEE	FFFFFFFFFF
MM	MM	TTTTTTTTT	AAAAAA	DDDDDDDD	EEEEEEEEEE	FFFFFFFFFF
MMM	MMM	TT	AA	DD	EE	FF
MMM	MMM	TT	AA	DD	EE	FF
MM	MM	TT	AA	DD	EE	FF
MM	MM	TT	AA	DD	EE	FF
MM	MM	TT	AA	DD	EEEEEEEE	FFFFFFFF
MM	MM	TT	AA	DD	EEEEEEEE	FFFFFFFF
MM	MM	TT	AAAAAAAAA	DD	EE	FF
MM	MM	TT	AAAAAAAAA	DD	EE	FF
MM	MM	TT	AA	DD	EE	FF
MM	MM	TT	AA	DD	EE	FF
MM	MM	TT	AA	DDDDDDDD	EEEEEEEEEE	FF
MM	MM	TT	AA	DDDDDDDD	EEEEEEEEEE	FF

....
....
....
....

88888888	333333	222222
88888888	333333	222222
88	33	22
88	33	22
88	33	22
88	33	22
88888888	33	22
88888888	33	22
88	33	22
88	33	22
88	33	22
88	33	22
88888888	333333	2222222222
88888888	333333	2222222222

Definition file for MTAACP compilation

Version: 'V04-000'

```
*****
*
*  COPYRIGHT (c) 1978, 1980, 1982, 1984 BY
*  DIGITAL EQUIPMENT CORPORATION, MAYNARD, MASSACHUSETTS.
*  ALL RIGHTS RESERVED.
*
*  THIS SOFTWARE IS FURNISHED UNDER A LICENSE AND MAY BE USED AND COPIED
*  ONLY IN ACCORDANCE WITH THE TERMS OF SUCH LICENSE AND WITH THE
*  INCLUSION OF THE ABOVE COPYRIGHT NOTICE. THIS SOFTWARE OR ANY OTHER
*  COPIES THEREOF MAY NOT BE PROVIDED OR OTHERWISE MADE AVAILABLE TO ANY
*  OTHER PERSON. NO TITLE TO AND OWNERSHIP OF THE SOFTWARE IS HEREBY
*  TRANSFERRED.
*
*  THE INFORMATION IN THIS SOFTWARE IS SUBJECT TO CHANGE WITHOUT NOTICE
*  AND SHOULD NOT BE CONSTRUED AS A COMMITMENT BY DIGITAL EQUIPMENT
*  CORPORATION.
*
*  DIGITAL ASSUMES NO RESPONSIBILITY FOR THE USE OR RELIABILITY OF ITS
*  SOFTWARE ON EQUIPMENT WHICH IS NOT SUPPLIED BY DIGITAL.
*
*****
```

++

FACILITY: MAGNETIC TAPE ACP

ABSTRACT:

These are the data structure definitions and random macros
used to compile the MTAACP.

ENVIRONMENT:

Starlet Operating System, including privileged system calls
and internal system subroutines.

--

Author: D. H. Gillespie, Creation date: 18-may-77 16:25

MODIFIED BY:

V03-006	MMD0178	Meg Dumont,	26-May-1983	15:14
		Fix to support new input to IOC\$CVT_DEVNAM		
V03-005	MMD0173	Meg Dumont,	9-May-1983	15:15
		Fix to make USER_STATUS consistently defined within module		
V03-004	MMD0145	Meg Dumont,	25-Apr-1983	18:14

Add HDR4 label, add some literals for scratch_offset
and file_spec_max

V03-003 MMD0119 Meg Dumont, 29-Mar-1983 0:44
Added misc def's common inside the MTAACP

V03-002 MMD0002 Meg Dumont, 5-Jan-1983 13:50
Add another field to be define for V3.0 systems

V03-001 MMD0001 Meg Dumont, 11-Nov-1982 10:44
Add VCB def for enable user EOT handling. Needed to work on V3.X

V02-008 DMW00075 David Michael Walp 8-Feb-1982
Added VVP\$(TIS)_ACCOUNT and changed _PROC_NAME to _USERNAME

V02-007 DMW00058 David Michael Walp 7-Dec-1981
Removed MAX_FILESTR_LEN

V02-006 DMW00047 David Michael Walp 30-Jul-1981
Removed MAX_ATTR_CODE for global ATRSC_MAX_CODE, added
assume MACRO

V02-005 DMW00028 David Michael Walp 30-Jul-1981
Remove MOUSV_NORDVOL1 Added MOUSV_CHKIFSPC

V02-004 DMW00027 David Michael Walp 20-Jul-1981
Added True and False

V02-003 DMW00020 David Michael Walp 26-May-1981
Added Work Area Sz which was a GLOBAL LITERAL from OPCOM.
Inceased MSGSIZE from 20 to 124, new OPCOM message format.

V02-002 MCN0018 Maria del C. Nasr 24-Jun-1980
Fix syntax error in the linkage definitions.

V02-001 REFORMAT Maria del C. Nasr 17-Jun-1980

A0103 MCN0003 Maria del C. Nasr 01-Oct-1979 14:45
Add HDR3 definition

A0102 MCN0002 Maria del C. Nasr 26-Sep-79 16:05
Change BUG_CHECK macro to use builtin BUGW.

A0102 SPR20439 D. H. Gillespie, 21-Nov-1978 13:21
add number of tape marks spaced

A0101 DGH0003 D. H. Gillespie 17-NOV-1978 10:00
change ERROR() [CODE] to ERROR [CODE] to be compatible with
new BLISS

```
! define common external registers
```

```
MACRO COMMON_REG = CURRENT_VCB = 11 : REF BBLOCKX;
```

```
MACRO GLOBAL_REG = CURRENT_VCB = 11X;
```

```
! define commonly used linkage
```

```
LINKAGE
```

```
COMMON_CALL      = CALL : GLOBAL(GLOBAL_REG),
NOPRES           = CALL : GLOBAL(GLOBAL_REG),
                  NOPRESERVE(0,1,2,3,4,5,6,7,8,9,10),
JSB              = JSB  : GLOBAL(GLOBAL_REG),
L$CLOSE_FILE     = JSB  : GLOBAL(GLOBAL_REG),
                  NOTUSED(2,3,4,5,6,7,8,9),
L$GET_REQ        = JSB  : GLOBAL(GLOBAL_REG),
                  NOTUSED(5,6,7,8,9,10),
L$GET_START_HDR  = JSB  : GLOBAL(GLOBAL_REG),
                  NOTUSED(2,3,4,5,6,7,8,9),
L$GTNEXT_VOL_RE  = JSB  : GLOBAL(GLOBAL_REG),
L$GTNEXT_VOL_WR  = JSB  : GLOBAL(GLOBAL_REG),
                  NOPRESERVE(2,3,4,5,6,7,8,9,10),
L$ISSUE_IO       = JSB  : GLOBAL(GLOBAL_REG),
                  NOTUSED(2,3,4,5,6,7,8,9,10),
L$NEXT_VOL_READ  = JSB  : GLOBAL(GLOBAL_REG),
                  NOPRESERVE(2,3,4,5,6,7,8,9,10),
L$NEXT_VOL_WRIT  = JSB  : GLOBAL(GLOBAL_REG),
                  NOPRESERVE(2,3,4,5,6,7,8,9,10),
L$PRINT_NOT_LAB  = JSB  : GLOBAL(GLOBAL_REG),
                  NOTUSED(5,6,7,8,9,10),
L$PRINT_OPR_MSG  = JSB  : GLOBAL(GLOBAL_REG),
                  NOTUSED(2,3,4,5,6,7,8,9,10),
L$REPOSITION     = JSB  : GLOBAL(GLOBAL_REG),
                  NOTUSED(2,3,4,5,6,7,8,9,10),
L$WRAP_AROUND    = JSB  : GLOBAL(GLOBAL_REG),
                  NOTUSED(2,3,4,5,6,7,8,9,10),
L$WRITE_HEADER   = JSB  : GLOBAL(GLOBAL_REG),
                  NOTUSED(7,8,9,10),
L$WRITE_TM       = JSB  : GLOBAL(GLOBAL_REG),
                  NOTUSED(2,3,4,5,6,7,8,9,10),
L$WRITE_TRAILER  = JSB  : GLOBAL(GLOBAL_REG),
                  NOTUSED(2,3,4,5,6,7,8,9,10),
L$IOC_CVT_DEVNAM = JSB (REGISTER=0,REGISTER=1,REGISTER=4,REGISTER=5; REGISTER=1) :
                  PRESERVE (2,3,4,5,6)
                  NOTUSED (7,8,9,10,11);
```

```
! define macro to extract size
```

```
MACRO $BYTESIZE(OFFSET,POSITION,WIDTH,SIGN) = WIDTH / 8 %;
```

```
! declare psect usage to minimize page breakage.
```

```
PSECT
```

```
OWN      = $LOCKEDD1$,
GLOBAL   = $LOCKEDD1$,
PLIT     = $CODE$ (EXECUTE);
```

! Declare VAX built in functions.

BUILTIN

CHMU,	! change mode to user (ERR_EXIT)
INSQUE,	! insert into queue
MOVTUC,	! translate strings and check for invalid characters
MTPR,	! move to privilege register (SET_IPL)
REMQUE,	! remove from queue
ROT;	! rotate longword

! Structure declarations used for system defined structures to
! save typing.

STRUCTURE

BBLOCK [O, P, S, E; N] =
 [N]
 (BBLOCK+O)<P,S,E>.

BBLOCKVECTOR [I, O, P, S, E; N, BS] =
 [N*BS]
 (BBLOCKVECTOR+(O+I*BS))<P,S,E>;

assorted macros used in fcp code

set processor IPL

MACRO SET_IPL (LEVEL) = MTPR (%REF (LEVEL), PR\$_IPL)%;

Declare code that must be locked into the working set.

MACRO LOCK_CODE
PSECT =
CODE = \$LOCKEDC1\$,
PLIT = \$LOCKEDC1\$,
OWN = \$LOCKEDD1\$,
GLOBAL = \$LOCKEDD1\$;
%;

***** NOTE: The following two macros violate the BLISS language definition
***** in that they make use of the value of SP while building the arg list.
***** It is the opinion of the bliss maintainers that this usage is safe
***** from planned future optimizations.

Macro to call the change mode to kernel system service.
Macro call format is 'KERNEL_CALL (ROUTINE, ARG1, ARG2, ...)'.

MACRO
KERNEL_CALL (R) =
BEGIN
EXTERNAL ROUTINE SYSSCMKRNL : ADDRESSING_MODE (ABSOLUTE);
BUILTIN SP;
SYSSCMKRNL(R, .SP, %LENGTH-1
%IF %LENGTH GTR 1 %THEN, %REMAINING %FI)
END%;

Macro to call the change mode to exec system service.
Macro call format is 'EXEC_CALL (ROUTINE, ARG1, ARG2, ...)'.

MACRO
EXEC_CALL (R) =
BEGIN
EXTERNAL ROUTINE SYSSCMEEXEC : ADDRESSING_MODE (ABSOLUTE);
BUILTIN SP;
SYSSCMEEXEC(R, .SP, %LENGTH-1
%IF %LENGTH GTR 1 %THEN, %REMAINING %FI)
END%;

Macro used to signal fatal errors (internal consistency checks).

MACRO
BUG_CHECK (CODE) =
BEGIN
BUILTIN BUGW;
EXTERNAL LITERAL %NAME('BUG\$_', CODE);

```
        BUGW(%NAME('BUGS_',CODE) OR 4);
    END
%;
```

```
! Macro to signal an error status and continue.
```

```
MACRO
    ERROR [CODE] =
        BEGIN
            EXTERNAL USER_STATUS : VECTOR [2];
            BEGIN
                MAP USER_STATUS : WORD;
                USER_STATUS = CODE;
            END;
        END
%;
```

```
! Macro to signal an error status and exit.
! Implemented as a call into a change mode to user instruction followed
! by a RET.
```

```
MACRO
    ERR_EXIT (CODE) =
        (CHMU(%REF (%IF %NULL (CODE) %THEN 0 %ELSE CODE %FI));)%;
```

```
! Macro to generate a string with a descriptor.
```

```
MACRO
    DESCRIPTOR (STRING) =
        UPLIT (%CHARCOUNT (STRING),
            UPLIT BYTE (STRING))%;
```

```
! Macro to return the number of actual parameters supplied to a routine
! call.
```

```
MACRO
    ACTUALCOUNT =
        BEGIN
            BUILTIN AP;
            (.AP)<0,8>
        END%;
```

```
! check to see that constants have not changed
! e.g. ASSUME (IRC$C_FIXOVHDSZ + 2, IRC$C_VAROVHDSZ);
```

```
MACRO ASSUME (A,B) =
    %IF $BYTEOFFSET(A) NEQ $BYTEOFFSET(B)
    %THEN %WARN('WARNING CONSTANT HAS CHANGED')
    %FI %;
```


this structure describes a free page block

```
! this structure describes a volume virtual page
```

```

1 This structure describes fixed data in the first virtual page belonging
2 to the volume.

```

```
ASSUME ( JIB$$_USERNAME, VVP$$_USERNAME );
ASSUME ( JIB$$_ACCOUNT, VVP$$_ACCOUNT );
```

[illegible]

! Random other definitions

! MOUNT_VOL flags

MACRO MOUSV_REWIND = 0,0,1,0%: ! rewind on mount
MACRO MOUSV_LBLCHECK = 0,1,1,0%: ! check label
MACRO MOUSV_CHKIFSPC = 0,2,1,0%: ! check label if operator specified
MACRO MOUSV_MOUNTERR = 0,3,1,0%: ! there was an error, force physical mount

LITERAL

! some world famous Boolean values

TRUE = 1,
FALSE = 0,

! these are the structure types

FVP_TYPE = 1,
VVP_TYPE = 2,

! this is the size of a mailbox message from the operator

WORK_AREA_SZ = 128,
MSGSIZE = 124, ! 4 = status, 4 = id, operator text,
! plus XOPCOM line (WORK_AREA_SZ - 4)

IOEFN = 1, ! event flag for I/O
EFN = 1, ! event flag for I/O
TIMEFN = 3, ! event flag for timer wait

EXEC_MODE = 1, ! exec_mode value
USER_MODE = 3, ! user_mode access
MAX_DEVNAM_LENGTH = 16, ! Set the maxium length that a devname
! can be with VMS
NO OF SUPPORT_ANSI_LABELS = 4, ! Number of supported ANSI labels
ANSI_CBSZ = 80, ! Size of the ANSI standard label
FILE_SPEC_MAX = 79, ! Maximum file specification length
! for VMS long file names (39.39)

0253

AH-BT13A-SE
 VAX/VMS V4.0

DIGITAL EQUIPMENT CORPORATION
CONFIDENTIAL AND PROPRIETARY